



## NAIT XS 2 Integrated Amplifier



### Overview:

At 70 Watts per channel, the NAIT XS 2 is more powerful than its NAIT XS predecessor. It also features numerous refinements to enhance its music making still further: ceramic heatsink technology, constant current source drive electronics, a reconfigured internal layout to optimise signal paths and custom manufactured film style capacitors in all audio critical locations.

Constructed in a slimline aluminium enclosure, the NAIT XS 2 provides six analogue inputs and the same innovative Class A headphone amplifier as the SUPERNAIT 2. With any amplifier, however, the proof of its technology is in the listening. The NAIT XS 2 is both powerful and delicate, dynamic and even-handed. It does everything the music asks and delivers everything that a Naim amplifier should.

### Features:

- 70W (into 8ohms) 100W (into 4ohms)
- 6 analogue inputs: 4 x DIN/RCA pair, 1 x RCA pair, 1 x DIN (for Naim phono amplifier)
- 1/4" (6.35mm) headphone output and high-quality Class-A headphone amplifier
- Constant current source circuit technique employed (introduced in NAC 552 preamplifier) to provide ultra-quiet drive signals for relays to improve sound quality
- Ceramic heat sink isolation for improved sound quality on power and preamp section
- Performance upgradable with FlatCap, HiCap or SuperCap power supplies
- Custom-designed toroidal transformer with seven separate windings
- Powered input for use with StageLine or SuperLine phono stages
- USB-mini B for future software upgrades
- British build and design

### Specification:

#### AUDIO INPUTS

Input Level	Suitable for 2V sources (0.5 to 5.0V)
Input Sensitivity	130mV
Analogue Inputs	4 x DIN/RCA pair, 1 x RCA pair, 1 x DIN (for Naim phono amplifier)
<b>USER CONTROL INTERFACE</b>	
Front Panel	Volume control and front panel buttons
<b>AUDIO OUTPUTS</b>	
Line Outputs Fixed (level)	AV (DIN), HDD (DIN) 130mV, 600?
Line Outputs Variable (level)	Pre-amp (DIN), sub (RCA pair), 775mV, 50?
Power Outputs	+24V for Naim phono amplifier
Headphone outputs	¼ inch (6.35mm) TRS Socket
<b>SPEAKER OUTPUTS</b>	
Power Output	70W per channel into 8?, 100W per channel into 4?
<b>UPGRADES</b>	
Power Supply	FlatCap, HiCap or Supercap
<b>CONNECTIVITY</b>	
Remote Control	Infra-Red (RC5)
Remote Input	1 x 3.5mm jack on rear
Updates	1 x USB mini-B
<b>POWER</b>	
Mains Supply	100V, 115V, 230V; 50 or 60Hz
Power Consumption (quiescent)	16VA
Power Consumption (maximum)	350VA
<b>PHYSICAL</b>	
Dimensions	70 x 432 x 314 (H x W x D)
Weight	8.4kg
Supplied With	NARCOM-4 remote control
<b>OTHER</b>	
Suggested System	CD5XS CD player or ND5 XS network player
<b>FINISH</b>	
Front	Brushed and black anodised aluminium
Case	Black powder coated aluminium

Please visit your nearest retailer for a demonstration:  
[naimaudio.com/find-a-retailer](http://naimaudio.com/find-a-retailer)



**Naim Audio Limited**

Southampton Road • Salisbury • England • SP1 2LN  
 Tel: +44 (0) 1722 426600 • Fax: +44 (0) 871 230 1012

[naimaudio.com](http://naimaudio.com)