



SUPERNAIT 2 Integrated Amplifier



Overview:

The SUPERNAIT 2 combines a muscular 80 Watts per channel power amplifier with six analogue inputs. In terms of both performance and hardware, it is conceptually as close as it is possible to get to separate pre and power amps in one box. It borrows advanced technology from Naim's flagship preamplifiers, the NAC 552, and in employing the latest Naim DR (Discrete Regulator) techniques in its power supply, sits right at the forefront of Naim amplifier technology. It is also constructed in the classic Naim full height extruded aluminium enclosure.

Features:

- 80W per channel (in 8 ohms), 130W per channel (into 4 ohms)
- Built in Naim DR (Discrete Regulator) supplying preamplifier section
- ¼" (6.35mm) headphone output and high-quality Class-A headphone amplifier
- Constant current source circuit technique employed (introduced in NAC 552 preamplifier) to provide ultra-quiet drive signals for relays to improve sound quality
- All inputs are individually decoupled and hand-wired for improved microphonic isolation (as per NAC 282 upwards)
- Ceramic heat sink isolation for improved sound quality on power and preamp section
- Performance upgradable via Naim FlatCap, HiCap or SuperCap power supplies
- Powered input for use with StageLine or SuperLine phono stages
- USB-mini B for future software upgrades
- British build and design

Specification:

AUDIO INPUTS

Input Level	Suitable for 2V sources (0.5 to 5.0V)
Input Sensitivity	130mV
Analogue Inputs	4 x DIN/RCA pair, 1 x RCA pair, 1 x DIN (for Naim phono amplifier)

USER CONTROL INTERFACE

Front Panel	Volume control, balance control and front panel buttons
-------------	---

AUDIO OUTPUTS

Line Outputs Fixed (level)	AV (DIN), HDD (DIN) 130mV, 600?
Line Outputs Variable (level)	Pre-amp (DIN), bi-amp (DIN), sub (RCA pair) 775mV, 50?
Power Output	+24V for Naim phono amplifier
Headphone outputs	¼ inch (6.35mm) TRS Socket

SPEAKER OUTPUTS

Power Output	80W per channel into 8?, 130W per channel into 4?
--------------	---

UPGRADES

Power Supply	FlatCap, HiCap or SuperCap
--------------	----------------------------

CONNECTIVITY

Remote Control	Infra-Red (RC5)
Remote Input	1 x 3.5mm jack on rear
Updates	1 x USB mini-B

POWER

Mains Supply	100V, 115V, 230V; 50 or 60Hz
Power Consumption (quiescent)	37VA
Power Consumption (maximum)	400VA

PHYSICAL

Dimensions	87 x 432 x 314 (H x W x D)
Weight	13.4kg
Supplied With	NARCOM-4 remote control

OTHER

Suggested System	CDX2 CD player or NDX network player
------------------	--------------------------------------

FINISH

Front	Brushed and black anodised aluminium
Case	Black powder coated aluminium

Reviews

Here is a selection of reviews that have been written about this product.

What Hi-Fi?-February 2014

"It delivers a huge slice of Naim's addictive sound at a still sensible price"

Please visit your nearest retailer for a demonstration:

naimaudio.com/find-a-retailer



Naim Audio Limited

Southampton Road • Salisbury • England • SP1 2LN
Tel: +44 (0) 1722 426600 • Fax: +44 (0) 871 230 1012

naimaudio.com

