

Bowers & Wilkins

CM Series



CM1 S2

The original CM speaker is back, and now it's better than ever. The CM1 S2 now comes with updated acoustic technologies that raise the bar for sonic performance, together with the same high quality finishes and materials found in the rest of the range. And all this from a speaker compact enough to fit almost anywhere.



Technical features Nautilus tube loaded Decoupled Double Dome aluminium tweeter
Kevlar® brand fibre cone bass / midrange
Flowport™

Description 2-way vented-box system

Drive units 1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency
1x ø130mm (5 in) woven Kevlar cone bass / midrange

Frequency range -6dB at 45Hz and 50kHz

Frequency response 50Hz - 28kHz ±3dB

Dispersion Within 2dB of reference response
Horizontal: over 60° arc
Vertical: over 10° arc

Sensitivity 84dB spl (2.83V, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)
<1% 110Hz - 22kHz

Nominal impedance 8Ω (minimum 4.0Ω)

Crossover frequency 4kHz

Recommended amplifier power 30W - 100W into 8Ω on unclipped programme

Max. recommended cable impedance 0.1Ω

Dimensions Height: 280mm (11 in)
Width: 165mm (6.5 in)
Depth: 260mm (10.2 in) cabinet only
276mm (10.9 in) including grille and terminals

Net weight 6.7kg (14.7 lb)

Finishes Cabinet: Grille:
Rosenut Black
Gloss Black Black
Satin White Grey