

Bowers & Wilkins

CM Series



CM5 S2

CM5 S2 is a traditionally sized standmounted speaker delivering a sound that's anything but conventional. Its large midrange/bass driver is ably supported by a Decoupled Double Dome tweeter, capable of revealing layers of pin-sharp musical detail.



Technical features Nautilus tube loaded Decoupled Double Dome aluminium tweeter
Kevlar® brand fibre cone bass / midrange
Flowport™

Description 2-way vented-box system

Drive units 1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency
1x ø165mm (6.5 in) woven Kevlar cone bass / midrange

Frequency range -6dB at 45Hz and 50kHz

Frequency response 50Hz - 28kHz ±3dB

Dispersion Within 2dB of reference response
Horizontal: over 60° arc
Vertical: over 10° arc

Sensitivity 88dB spl (2.83V, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)
<1% 100Hz - 22kHz
<0.5% 150Hz - 20kHz

Nominal impedance 8Ω (minimum 3.7Ω)

Crossover frequency 4kHz

Recommended amplifier power 30W - 120W into 8Ω on unclipped programme

Max. recommended cable impedance 0.1Ω

Dimensions Height: 340mm (13.4 in)
Width: 200mm (7.9 in)
Depth: 285mm (11.2 in) cabinet only
301mm (11.9 in) including grille and terminals

Net weight 8.9kg (19.6 lb)

Finishes Cabinet: Grille:
Rosnut Black
Gloss Black Black
Satin White Grey