UTOPIA Product data sheet



Utopia are the ultimate Focal headphones. They are the brand's flagship product, combining the best of our technologies with assertive design, to enhance your listening experience.

Their full-range, Beryllium, 'M'-shaped speaker drivers are fully open-backed and run with no passive or active correction, from 5 Hz to over 50 kHz! The listening experience they deliver is strikingly real, precise and dynamic, with a soundstage that is both wide and deep: close your eyes and feel the musicians beside you. Combining comfort and aesthetics, Utopia delivers uncompromising design and conception. The forged, recycled carbon yokes are modern and sophisticated in style, whilst providing more lightness. The honeycomb grille and Black Chrome ring showcase subtle design details, like the Yin & Yang on the outer case, the black and red double grille on the speaker driver, and more.

So many elements that fiercely embody Utopia: the perfect balance between technology and design!



Key points

- High-end, open-back, high-fidelity headphones; for home use
- Full-range speaker driver with 'M'-shaped, pure Beryllium dome: pure, dynamic and perfectly balanced sound
- Made in France in the Focal workshops
- Design that adapts to all head morphologies: optimum comfort
- Premium materials and sophisticated finishes: genuine leather, forged, recycled carbon, aluminium, etc.

Impedance80 OhmsSensitivity104dB SPL / 1mW @ 1kHzTHD<0.2 % @ 1kHz / 100dB SPLFrequency response5Hz - 50kHzSpeaker driver11/46" (40mm) pure beryllium 'M'-shaped domeWeight1.08lbs (490g)Cable provided• 1 x 5ft cable (1.5m) with 1 x ½" (3.5mm) asymmetric TRS Jack connector and 2 x Lemo® connectors • 1 x 10ft cable (3m) with 1 x symmetrical 4-point XLR connector and 2 Lemo® connectors • 1 x Jack adapter, ½" (3.5mm) point socket - ½" (6.35mm) point plugCarrying case included9.8x9.4x4.7" (25x24x12cm)	Type	Circum-aural, open-back headphones
THD <0.2 % @ 1kHz / 100dB SPL Frequency response 5Hz - 50kHz Speaker driver 11%6" (40mm) pure beryllium 'M'-shaped dome Weight 1.08lbs (490g) Cable provided 1 x 5ft cable (1.5m) with 1 x 1/6" (3.5mm) asymmetric TRS Jack connector and 2 x Lemo® connectors 1 x 10ft cable (3m) with 1 x symmetrical 4-point XLR connector and 2 Lemo® connectors 1 x Jack adapter, 1/8" (3.5mm) point socket - 1/4" (6.35mm) point plug	Impedance	80 Ohms
Frequency response 5Hz - 50kHz Speaker driver 11%" (40mm) pure beryllium 'M'-shaped dome Weight 1.08lbs (490g) Cable provided 1.05 to cable (1.5m) with 1 x 1/2" (3.5mm) asymmetric TRS Jack connector and 2 x Lemo® connectors 1 x 10ft cable (3m) with 1 x symmetrical 4-point XLR connector and 2 Lemo® connectors 1 x Jack adapter, 1/2" (3.5mm) point socket - 1/4" (6.35mm) point plug	Sensitivity	104dB SPL / 1mW @ 1kHz
Speaker driver 11/46" (40mm) pure beryllium 'M'-shaped dome Weight 1.08lbs (490g) 1.08lbs	THD	<0.2 % @ 1kHz / 100dB SPL
Weight 1.08lbs (490g) 1.08lb	Frequency response	5Hz - 50kHz
• 1 x 5ft cable (1.5m) with 1 x 1/8" (3.5mm) asymmetric TRS Jack connector and 2 x Lemo® connectors • 1 x 10ft cable (3m) with 1 x symmetrical 4-point XLR connector and 2 Lemo® connectors • 1 x Jack adapter, 1/8" (3.5mm) point socket - 1/4" (6.35mm) point plug	Speaker driver	1%ε" (40mm) pure beryllium 'M'-shaped dome
Cable provided • 1 x 10ft cable (3m) with 1 x symmetrical 4-point XLR connector and 2 Lemo® connectors • 1 x Jack adapter, 1/4" (3.5mm) point socket - 1/4" (6.35mm) point plug	Weight	1.08lbs (490g)
Carrying case included 9.8x9.4x4.7" (25x24x12cm)	Cable provided	• 1 x 10ft cable (3m) with 1 x symmetrical 4-point XLR connector and 2 Lemo® connectors
	Carrying case included	9.8x9.4x4.7" (25x24x12cm)

