

FREEDOM AND PERFORMANCE

Airship II

REL
ACOUSTICS LTD

Airship II elevates REL's reputation for edge of the art wireless connection in the audio industry to new heights. Taking advantage of a new Texas Instruments DAC/ADC design, noise on the system drops by 12 dB. Yet it is the effect of this that is transformative. Sound travelling through 40, 50, even 60 feet arrives clear, crisp, dynamic and possessing richly saturated tonal colours.

Offers High Level Input, Low Level Input, .1/LFE-RCA and .1/LFE XLR balanced inputs. .1 and High Level may run concurrently for REL Theatre Reference performance.

For those who want all the performance of models Serie S and Reference but simply cannot use conventional cable, help has arrived. Airship II is a quiet revolution that must be heard to be believed. Utterly brilliant.



SPECIFICATIONS

XLR .1/LFE INPUT IMPEDENCE	10k ohms	POWER CONSUMPTION	600 mWatts
WIRELESS OUTPUT POWER	less than -3dBm	FINISH	Matte Black
MAINS INPUT VOLTAGE	5V DC, 5.5mm circular connector, positive center	WIRELESS EFFECTIVE DISTANCE	30 feet (10 meters) with clear line of site
INPUT CONNECTORS	High-Level Neutrik Speakon, L/R Low-Level RCA, LFE single phono RCA, LFE balanced XLR	W x H x D	TRANSMITTER 6 x 6 x 2 5/8 in., (152.4 x 152.4 x 66.7 mm) Receiver 5 1/2 x 4 5/16 x 1 3/16 in., (139.7 x 109.5 x 30 mm)

All RELs - Fully Electronic SET-SAFE, output short, DC Fault

Join the Pursuit™ | rel.net