DALI

RUBIKORE 2

Rich on detail with an impressive soundstage

The DALI RUBIKORE 2 stand-mount loudspeaker offers the ideal blend of compact size and generous sound. Its immensely rigid cabinet forms the perfect foundation to enable its ultra-light 29 mm soft dome tweeter and 6½ inch low-loss, Clarity Cone™ wood fibre driver to perform optimally. The result is a system characteriesd by intense clarity, expansive imagery and generous bass with both precision and timing.

EVOLUTION THROUGH KORE TECHNOLOGY

The RUBIKORE 2 employs DALI KORE inspired Clarity Cone™ Technology, an SMC driver, a brand new Low-Loss dome tweeter without ferrofluid and a Continuous Flare Technology bass reflex port to maximise performance and high-end sound quality.

EXCEPTIONAL ACOUSTIC PERFORMANCE

The RUBIKORE 2 brings DALI KORE inspired technology and performance to a compact stand, shelf or furniture mount loudspeaker. Designed to provide high-end sound quality in smaller rooms, the RUBIKORE 2 combines a 6½ inch paper and wood fibre Clarity Cone™ Technology SMC bass/midrange driver with a DALI designed, ultra low loss, lightweight dome tweeter. The result is exceptional, wide dispersion, low loss sound for even the smallest of listening spaces.

DANISH FURNITURE DESIGN AND HIGH-END FINISHES

The long tradition of Danish joinery and cabinet making craft is fully expressed in the RUBIKORE 2. Its stand or shelf-mount dimensions result in a compact and stylish design that emphasises the exquisite craftsmanship and finishing. In addition to aesthetic beauty, the internally braced RUBIKORE 2 cabinet also provides the immensely rigid and inert platform that high performance electro-acoustics demands.

HAND-CRAFTED BY DALI

The RUBIKORE 2 is hand-crafted and assembled at DALI in Denmark and is predominantly a product of in-house skill, expertise, design, and manufacture. But in addition to its Danish assembly, the RUBIKORE 2 also calls on numerous nearby component suppliers and skills to reinforce its fully Danish roots. The RUBIKORE 2 is Danish to the core.





IN ADMIRATION OF MUSIC

RUBIKORE-ONEPAGERs.indd 1 24/05/2024 11:31 AM

TECHNICAL SPECIFICATIONS

See the full DALI PHANTOM range on dali-speakers.com

DALI RUBIKORE	RUBIKORE 2
Frequency range	50 - 26,000 Hz ±3 dB
Sensitivity	87 dB@1mfor 2.83 V
Nominal impedance	4 ohm
Maximum SPL	107 dB
Crossover frequency	2,800 Hz
Crossover principle	2-way
Recommended amplifier power	40 - 150 Watt
High frequency driver(s)	1 x 29 mm low loss soft dome
High frequency diaphragm	Soft woven fabric
Low/Mid frequency driver(s) Low/mid frequency diaphragm	1 x 6½ inch Clarity Cone™ paper and wood fibre
Connection input(s)	Bi-wire / Bi-amp
Enclosure type	Bass reflex
Bass reflex tuning frequency	44 Hz
Other features	N/A
Recommended placement	Stand / Shelf
Recommended distance from rear wall	20 - 120 cm
Dimensions (H x W x D)	350 x 195 x 335 mm 13.9 x 7.7 x 13.3 inches
Weight incl. grille	9.5 kg 20.9 lb
Shipping weight	10.5 kg 23.1 lb
Finishes	High Gloss Black High Gloss Maroon Natural Walnut High Gloss White
Accessories	Manual Rubber feet Polishing cloth (high gloss finish only) Front grille
Spike thread size	M8

















Scan QR code for more information

DALI A/S WWW.DALI-SPEAKERS.COM