DALI

RUBIKORE 8

Epic soundstage with powerful dynamics and transperancy

Upping the audio ante to the max, the DALI RUBIKORE 8 can generate stunning musical soundscapes with ease. Its immensely powerful trio of woofers integrate the bass and midrange bands seamlessly, while the detail and wide dispersion of its DALI Hybrid Tweeter help it fill even the largest listening spaces with rich clarity and pin-sharp imaging. The RUBIKORE 8 represents the pinnacle of the RUBIKORE entry into pure high-end sound, but at a midrange price adds immense musical detail and clarity.

EVOLUTION THROUGH KORE TECHNOLOGY

Inspired by the DALI KORE, the RUBIKORE 8 employs Clarity Cone[™] Technology, SMC drivers, SMC-KORE[™] inductors, a Hybrid Tweeter module with a brand new Low-Loss dome tweeter without ferrofluid and Continuous Flare bass reflex ports to maximise its performance and high-end sound quality.

EXCEPTIONAL ACOUSTIC PERFORMANCE

The RUBIKORE 8 is a wide bandwidth, floor-stand loudspeaker packed with DALI KORE inspired technology. In its element in large room, high-end stereo music systems, or in the front channel role of ambitious home theatres, the RUBIKORE 8 combines three 6½ inch paper and wood fibre Clarity Cone™ Technology SMC bass/midrange drivers to deliver a hugely accomplished musical performance. A DALI Hybrid dome and planar tweeter dovetails perfectly with the bass/midrange drivers to add stupendous high frequency detail and clarity. The RUBIKORE 8 excels at relaxed, large scale, wide dispersion, low loss and amplifier optimised sound quality.

DANISH FURNITURE DESIGN AND HIGH-END FINISHES

The RUBIKORE 8 combines its remarkable sound quality with elegant, low-resonance enclosure engineering and a luxurious Danish designed and hand-built cabinet, available in four exclusive finishes.

HAND-CRAFTED BY DALI

Each RUBIKORE 8 is individually crafted, assembled and tested at DALI in Denmark using as many locally sourced components as possible.





IN ADMIRATION OF MUSIC

RUBIKORE-ONEPAGERs.indd 5 24/05/2024 11:32 AM

TECHNICAL SPECIFICATIONS

See the full DALI PHANTOM range on dali-speakers.com

DALI RUBIKORE	RUBIKORE 8	
Frequency range	38 - 34,000 Hz ±3 dB	
Sensitivity	90.5 dB@1mfor2.83 V	
Nominal impedance	4 ohm	
Maximum SPL	112 dB	
Crossover frequency	500 / 800 / 2,400 / 14,000 Hz	
Crossover principle	2½ + ½ + ½-way	
Recommended amplifier power	40 - 250 Watt	
High frequency driver(s)	17×45 mm planar magnetostatic tweeter 1×29 mm low loss soft dome	
High frequency diaphragm	Planar magnetostatic Soft woven fabric	
Low/Mid frequency driver(s) Low/mid frequency diaphragm	3 x 6½ inch Clarity Cone™ paper and wood fibre	
Connection input(s)	Bi-wire / Bi-amp	
Enclosure type	Bass reflex	
Bass reflex tuning frequency	33 Hz	
Other features	N/A	
Recommended placement	Floor	
Recommended distance from rear wall	25 - 180 cm	
Dimensions (H x W x D)	1100 x 220 x 444 mm 43.5 x 8.7 x 17.6 inches	
Weight incl. grille	30 kg 66.1 lb	
Shipping weight	33 kg 72.7 lb	
Finishes	High Gloss Black High Gloss Maroon Natural Walnut High Gloss White	
Accessories	Manual Polishing cloth (high gloss finish only) Front grille Premium spike set	
Spike thread size	M8	
















Scan QR code for more information

DALI A/S WWW.DALI-SPEAKERS.COM