DALI

RUBIKORE CINEMA

The ultimate compact and powerful LCR home cinema loudspeaker

The DALI RUBIKORE CINEMA strikes a perfect balance between versitility, size and performance to be the ultimate DALI LCR loudspeaker. Its two 6½-inch low-loss, Clarity Cone™, wood fibre woofers deliver both expansive, extended bass, and the transparently explicit midrange quality so vital for centre channel roles. And the rotatable Hybrid Tweeter module adds wide dispersion, high frequency finesse and detail, on top of both portrait and landscape mounting options. The RUBIKORE CINEMA is a full-blown LCR solution for the highest performance home cinema systems.

EVOLUTION THROUGH KORE TECHNOLOGY

The RUBIKORE CINEMA brings multiple DALI KORE loudspeaker technologies to the home theatre front and centre channel roles. Its Clarity Cone™ Technology bass/midrange driver diaphragm helps ensure natural midrange clarity, free from colouration, while its DALI SMC motor systems minimise driver distortions and losses. In addition to its rotatable Hybrid dome and planar tweeter, within its crossover circuits, the RUBIKORE CINEMA employs audiophile grade Mundorf™ capacitors to reduce losses still further.

EXCEPTIONAL ACOUSTIC PERFORMANCE

The RUBIKORE CINEMA brings high performance loudspeaker solutions to the left, centre and right channel roles in home theatre systems where brilliant, high-end sound quality is non-negotiable.

DANISH FURNITURE DESIGN AND HIGH-END FINISHES

The long tradition of Danish joinery and cabinet making craft is fully expressed in the RUBIKORE CINEMA. Its versatile cabinet design is able to accommodates both landscape and portrait orientation and is exquisitely crated and finished. And In parallel with its aesthetic quality, the RUBIKORE CINEMA cabinet also provides the immensely rigid and inert platform that high performance electro-acoustics demands.

HAND-CRAFTED BY DALI

The RUBIKORE CINEMA is hand-crafted and assembled at DALI in Denmark and is predominantly a product of in-house skill, expertise, design, and manufacture. But in addition to its Danish assembly, the RUBIKORE CINEMA also calls on numerous nearby component suppliers and skills to reinforce its fully Danish roots. The RUBIKORE CINEMA is Danish to the core.





IN ADMIRATION OF MUSIC

RUBIKORE-ONEPAGERs.indd 9 24/05/2024 11:33 AM

TECHNICAL SPECIFICATIONS



See the full DALI PHANTOM range on dali-speakers.com

DALI RUBIKORE	RUBIKORE CINEMA
Frequency range	49 - 34,000 Hz ±3 dB
Sensitivity	89 dB@1mfor 2.83 V
Nominal impedance	4 ohm
Maximum SPL	111 dB
Crossover frequency	2,800 / 14,000 Hz
Crossover principle	2 + ½-way
Recommended amplifier power	40 - 200 Watt
High frequency driver(s)	17 x 45 mm planar magnetostatic tweeter 1 x 29 mm soft dome
High frequency diaphragm	Planar magnetostatic Soft woven fabric
Low/Mid frequency driver(s) Low/mid frequency diaphragm	2 x 6½ inch Clarity Cone™ paper and wood fibre
Connection input(s)	Bi-wire / Bi-amp
Enclosure type	Bass reflex
Bass reflex tuning frequency	36 Hz
Other features	Rotatable Hybrid Tweeter module
Recommended placement	Stand / Shelf
Recommended distance from rear wall	5 - 100 cm
Dimensions (H x W x D)	197 x 581 x 400 mm 7.7 x 22.8 x 15.7 inches
Weight incl. grille	16 kg 35.2 lb
Shipping weight	17.5 kg 38.5 lb
Finishes	High Gloss Black Natural Walnut High Gloss White
Accessories	Manual Rubber feet Polishing cloth (high gloss finish only) Front grille
Spike thread size	N/A



High Gloss Black







High Gloss Maroon



All technical specifications are subject to change without notice.

High Gloss White

Scan QR code for more information

DALI A/S WWW.DALI-SPEAKERS.COM

RUBIKORE-ONEPAGERs.indd 10 24/05/2024 11:33 AM