

**NEW!
2024**

DALI

RUBIKORE ON-WALL

Wide dynamic range and coherent, detailed sound – On the wall

The DALI RUBIKORE ON-WALL is a versatile multipurpose performer. Its 6½-inch Clarity Cone™ wood fibre woofer and rotatable DALI Hybrid Tweeter are integrated into a neatly engineered low-profile wall-mount enclosure that ingeniously employs the wall as part of its reflex port for deeply impressive bass. The ON-WALL is ideal for both stereo and multichannel roles and in both it delivers fabulously detailed and expansive, wide bandwidth, high performance sound.

EVOLUTION THROUGH KORE TECHNOLOGY

The RUBIKORE ON-WALL is not only one of the most versatile high-end, high performance loudspeakers available, it is unique in employing multiple DALI KORE inspired technologies.

Its Clarity Cone™ Technology bass/midrange driver diaphragm helps ensure natural midrange clarity, free from colouration, while its DALI SMC motor systems minimise driver distortions and losses. And within its crossover circuits, the RUBIKORE ON-WALL employs audiophile grade Mundorf™ capacitors to reduce losses still further. Also inspired by the EVO-K Hybrid Tweeter used in the DALI KORE, the RUBIKORE ON-WALL uses a new Low-Loss dome tweeter without ferrofluid in the magnet gap, for ultimate resolution in the high frequencies. Last but not least, the Hybrid Tweeter module can be rotated for use in both portrait or horizontal mode.

EXCEPTIONAL ACOUSTIC PERFORMANCE

The RUBIKORE ON-WALL is a space-saving, high performance loudspeaker solution for almost any application. It combines immense versatility with stunning high-end sound quality - for the wall.

DANISH FURNITURE DESIGN AND HIGH-END FINISHES

The RUBIKORE ON-WALL combines remarkable sound quality with an elegant, unintrusive and low-resonance enclosure, both luxurious, stylish and Danish designed.

HAND-CRAFTED BY DALI

Each RUBIKORE ON-WALL is individually crafted, assembled and tested at DALI in Denmark using as many locally sourced components as possible.



DALI


IN ADMIRATION OF MUSIC

TECHNICAL SPECIFICATIONS



See the full DALI PHANTOM range on dali-speakers.com

DALI RUBIKORE	RUBIKORE ON-WALL
Frequency range	59 - 34,000 Hz ±3 dB
Sensitivity	88.5 dB @ 1 m for 2.83 V
Nominal impedance	4 ohm
Maximum SPL	108 dB
Crossover frequency	2,900 / 14,000 Hz
Crossover principle	2 + ½-way
Recommended amplifier power	20 - 150 Watt
High frequency driver(s)	17 x 45 mm planar magnetostatic tweeter 1 x 29 mm low loss soft dome
High frequency diaphragm	Planar magnetostatic Soft woven fabric
Low/Mid frequency driver(s) Low/mid frequency diaphragm	1 x 6½ inch Clarity Cone™ paper and wood fibre
Connection input(s)	Single Wire
Enclosure type	Bass reflex
Bass reflex tuning frequency	49 Hz
Other features	Rotatable Hybrid Tweeter module
Recommended placement	On-wall / Shelf
Recommended distance from rear wall	0 - 30 cm
Dimensions (H x W x D)	465 x 278 x 142 mm 18.4 x 11.0 x 5.6 inches
Weight incl. grille	8.5 kg 18.7 lb
Shipping weight	9.5 kg 20.9 lb
Finishes	High Gloss Black Natural Walnut High Gloss White
Accessories	Manual Rubber feet Polishing cloth (high gloss finish only) Front grille
Spike thread size	N/A




High Gloss Black




High Gloss White



Natural Walnut



High Gloss Maroon



Scan QR code for more information