

MR1 MK3 Desktop Speaker System



Audio

Frequency response

48Hz - 22kHz (typical in-room)

Speaker units

2 x Ruark 20mm silk dome tweeters
2 x Ruark 85mm NS+ woofers

Amplifier

2 x 25W nominal Class D

Enhancements

Adaptive EQ
Soft-clip overload protection

Cabinet type

Dual-flared tuned bass-reflex

Cabinet volume

2.0 litres

Tuning frequency

68Hz

Crossover frequency

2.5kHz

Connectivity

Bluetooth

V5.1, aptX HD, SBC, AAC

Line-input/optical-input

Combined 3.5mm stereo jack & mini Toslink (24-bit/192kHz PCM)

Turntable input

RCA input with MM phono stage (max 7mv)

Subwoofer-output

Subwoofer output via mono RCA

USB-C audio input

Up to 24-bit/96kHz UAC 1.0

Features

Adjustable input levels

Line-in, phono-in, USB & optical

Remote control

Compact IR remote

Auto-standby

Auto-standby and wake-up

General specifications

Standard finishes

Charcoal cabinet with Dark Slate fabric grille
Rich Walnut cabinet with Dark Slate fabric grille

Product dimensions (cabinet)

H185 x W135 x D160mm each

Product dimensions (max)

(inc feet, controls & cables)
H200 x W135 x D185mm each

Product weight

2.1kg each

Carton dimensions

H290 x W395 x D190mm

Packaged weight

5.5kg

Product power input

18VDC 2.8A
3.5 x 1.35mm DC jack socket

AC power adaptor

100-240VAC 50-60Hz input
18VDC 2.8A output (1.8m lead)

Power consumption

0.5W standby
7W typical

In the box

MR1 MK3 (pair)
AC power adaptor
Quick start guide
3m Interconnect speaker cable
Compact IR remote



Rich
Walnut



Charcoal
Lacquer